

Back to Back - Plastic Hook & Velour Premium

Nr. 012

Composition

Rev. 01/2020

construction composition plastic hook and velour laminated back-to-back
100% polyamide

Technical properties

standard widths (mm) 16, 20, 25, 30, 38, 50, 75, 100, 150 +/-0.05mm
all widths between 3 and 320mm can be supplied upon request

colours black, white
other colours available upon request

selvedges no selvedges

thickness 2,5mm (+/-0,05mm)

hook density 355 hooks / square cm² (± 5%)

weight 500gr/m² ±10%

suitable temperature from - 30°C to +130°C

strength

| <u>cycles</u> | <u>peel strength</u> | <u>shear strength</u> |
|---------------|----------------------|-----------------------|
| 1 | 0,49 N/cm | 8,0 N/cm ² |
| 1000 | 0,29 N/cm | 7,8 N/cm ² |
| 3000 | 0,24 N/cm | 7,3 N/cm ² |

cleaning instructions

clean fasteners in closed position
to protect H&L fastener and the laundry



All information on this technical data sheet are based on reliable tests and are up-to-date at the date of issue. We serve ourselves the right to subject the products to technical changes without prior notice. We cannot fully control or anticipate the conditions under which this product may be used, each user should review and test the information in specific context of the planned use. To the maximum extent permitted by law, we will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet.